



CITYLIGHT

DDK-LED SLL PRODUCT RANGE

BASIC PARAMETERS

Light Source	LED
IP Rating	IP65
CRI (Ra>)	70
Beam angle °	120°
Luminous Efficiency (lm/W)	90
Warranty (Year)	5
Service Lifetime (hrs)	> 80 000
Color temperature (CCT)	5000 K
Colour	Aluminium / Grey
Material	Aluminium Alloy
LED light source	EPISTAR
Driver	DDK-LED
Operating Temp. °C	-20/+60
Input Voltage	AC220V ; 50-60Hz
Certification	CE, RoHS
Photometric test	acc. STN EN 13032
Photometric Lab	



DDK - LED SLL - represents IP65 LED luminaire designed especially for outdoor use.

Using high quality LED chips extends the lifetime for more than 80,000 hours. Luminous efficacy 90 lm / W guarantees optimal technical parameters. The high value of CRI> 70 Ra brings visual display required for lighting outdoor areas.

Features:

- Aluminum alloy
- The low-cost option
- Energy efficiency class A +
- Installation on pole / wall mount
- Luminous efficacy 90 lm / W
- Quality LED Chips EPISTAR
- Durable, long lifetime up to 80 000 hours
- Waterproof and dustproof, maintenance-free
- No UV or IR radiation, no mercury pollution

Applications:

Streets, roads, sidewalks, parking lots, residential areas and other outdoor spaces.



Type	Power +/-2%	Lumen +/- 9,3%	Color rendering index	Beam Angle °	CCT +/- 100K
DDK-SLL 30	30	> 2700	70	120	5000K
DDK-SLL 50	50	> 4500	70	120	5000K
DDK-SLL 70	70	> 6300	70	120	5000K
DDK-SLL 90	90	> 8100	70	120	5000K



www.ddk-led.eu

ddkLED
TECHNOLOGY SERVICES

business@ddk-led.eu

