



OFFICE & PUBLIC SPACE

DDK-LED DL 30W HQ (DOWNLIGHT)

BASIC PARAMETERS

Light Source	LED
IP Rating	IP 44
CCT	4000
CRI (Ra>)	75
Luminous flux (lm)	2700
Luminous efficacy (lm/W)	90
Beam Angle	120°
Warranty (Year)	2
LED Operating Life	> 50 000 hrs
Material	Aluminium
Color	Biela
LED Source	Epistar
Operating Temp.	-25/+45 °C
Input Voltage	AC85-265V
Certification	CE, PSE, RoHS, SAA, UL
Photometric test	acc.STN EN 13032
Photometric Lab.	Skúšobňa FEI STU, Ilkovičova 3, BA



DDK-LED DL 30W HQ (Downlight) - presents the new high performance LED downlight designed for installation directly into the plasterboard or coffered ceilings. Excellent thermal management and the material extend LED lifetime up to 50,000 hours. Easy installation, the best quality value and performance.

Features:
energy class A +
luminous efficacy of 90 lm / W
Instant on / off
no UV / flicker
easy installation

Applications:
offices, boutiques, receptions, shops, showrooms,
entrance halls, corridors



Type	Power +/-10%	Lumen +/- 9,3%	Color Rendering Index	Color temperature +/-100K	Diameter Ø
	(W)	(lm)	CRI (Ra)	CCT (K)	mm x H
DDK-LED DL 30 HQ	30	2700	> 75	NW (4000K)	Ø223xH80



www.ddk-led.eu

ddk-LED
TECHNOLOGY SERVICES

business@ddk-led.eu

