



STADIUM

DDK - LED VARIFLOOD PRODUCT RANGE

BASIC PARAMETERS

Light Source	LED
IP Rating	IP 66
CRI (Ra>)	70
Warranty (Year)	5
Service Lifetime	100 000
Efficiency	135/145 lm/W
CCT	4000 K
Material	Structure: Extruded ADC12 / Finish: Powder coated / Lens: Polycarbonate / Glass: Tempered glass
Color	matte black
Operating Temp.	40°C - 55°C
Input Voltage	180-305VAC
Certification	CE, GS, RoHS, UL
Photometric test	acc.STN EN 13032
Photometric Lab.	Skúšobňa FEI STU, Ilkovičova 3, BA



DDK-LED VARIFLOOD represents the group of high quality LED luminaires which are most suitable for all kinds of sport areas like stadiums (indoor and outdoor), racetracks, tunnels, and airports. They are applicable for indoor and outdoor areas due to protection degree up to IP 66. The power range is 470,705,940W at CCT 4000K. Using LED light source offers the operating lifetime up to 100 000 hours. Value index CRI >70Ra brings optical performance that shows excellent high output of any beam angle.

Feature




- Energy class A+
- Extreme power LED light
- Ultra efficiency lens technology
- Top quality materials used
- ies / ldt files are available on request
- Supplied complete with accessories
- Suspended / Surfaced mounting

Application:

- stadiums (indoor & outdoor)
- racetracks
- tunnels
- airports



Type	Power (W)	Lumen (lm)	Angle °	Efficiency
DDK - LED VARIFLOOD 470	470	68150	15° / 30°	145
DDK - LED VARIFLOOD 705	705	102225	15° / 30°	145
DDK - LED VARIFLOOD 940	940	136300	15° / 30°	145
DDK - LED VARIFLOOD 470	470	63450	15° / 30°	135
DDK - LED VARIFLOOD 705	705	95175	15° / 30°	135
DDK - LED VARIFLOOD 940	940	126900	15° / 30°	135



www.ddk-led.eu

ddk•LED
TECHNOLOGY SERVICES

business@ddk-led.eu

